



NOTES:

1. Return panel 1/2" glass bite may vary up to +3/16" / -1/4" as necessary to facilitate the use of standard glass sizes or to configure for out-of-plumb or out-of-square conditions.
2. The 4033 strike jamb magnet (4" long) should be centered in the jamb with V-314 jamb seal vinyl above and below it (see detail).
3. If 1/4" thick door glass is used in place of the standard 3/16" thickness, then substitute V-308 vinyl in place of the V-257 glazing vinyl.
4. Fractional dimensions rounded to the nearest 1/16". Actual unit sizes may vary up to 1/8" due to rounding or use of standard glass sizes.
5. Application of tolerances may affect glass and horizontal frame member sizes.
6. Centerline dimension refers to measurements taken at the center of the shower curb.

GLASS THICKNESS	PANEL GLAZING VINYL	
	VERTICAL	HORIZONTAL
1/4"	V-219	V-220
3/16"	V-226	V-225

1/2 SIZE DETAIL

SERIES

392

FRAMELESS
STIKSTALL

NOTE: Glazing material for all KD units and Glazed units must conform to Ansi Z97.1 and CPSC Standard 16 CFC 1201 Category I and II.

HORIZONTAL CROSS SECTION

EPH-N00-06125
DATE: 3-14-05



BATH ENCLOSURES

a product of ALCOA

PO Box 40 - Magnolia, AR 71754-0040 - (870) 234-4260
www.alumaxbath.com