



PANEL GLAZING VINYL		
GLASS THICKNESS	VERTICAL	HORIZONTAL
1/4"	V-219	V-220
3/16"	V-226	V-225

- NOTES:**
1. Panel 1/2" glass bite may vary up to +3/16" / -1/4" as necessary to facilitate the use of standard glass sizes or to configure for out-of-plumb or out-of-square conditions.
 2. The 4033 strike jamb magnet (4" long) should be centered in the jamb with V-314 jamb seal vinyl above and below it (see detail).
 3. If 1/4" thick door glass is used in place of the standard 3/16" thickness, then substitute V-308 vinyl in place of the V-257 glazing vinyl.
 4. Fractional dimensions rounded to the nearest 1/16". Actual unit sizes may vary up to 1/8" due to rounding or use of standard glass sizes.
 5. Application of tolerances may affect glass and horizontal frame member sizes.
 6. Centerline dimension refers to measurements taken at the center of the shower curb.

NOTE: Glazing material for all KD units and Glazed units must conform to Ansl Z97.1 and CPSC Standard 16 CFC 1201 Category I and II.

393
FRAMELESS
STIKSTALL

ALUMAX
BATH ENCLOSURES
a product of ALCOA
PO Box 40 - Magnolia, AR 71754-0040 - (870) 234-4260
www.alumaxbath.com

SERIES

1/2 SIZE DETAIL

HORIZONTAL CROSS SECTION

EPH-N00-06127
DATE: 3-14-05