



# ALUMAX

## BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514  
Fax: 870-234-3181

# 1040/1050 Slider Shower Door-Frameless

[www.alumaxbath.com](http://www.alumaxbath.com)

## Product Features

Available in standard and custom configuration  
3/8 Tempered safety glass  
Adjustable sealed heavy duty ball bearing rollers  
Up and down adjustment of panels is  $\pm .156$   
Safety tee-lock wall jamb to header connection  
Pocketed wall jambs for superior leak prevention  
Transparent molded panel guide for inconspicuous control of sliding panels

## Options

Anti-jamb header insert  
Wall fill  
Curb fill  
Glass patterns  
Finish



## Calculations

Maximum allowable width of unit = 72 (@ 71 1/4 tall)  
Maximum allowable height of unit = 84 (@ 60 wide)

## Glass Size

Width = (Unit Width  $\div$  2) + 1/4  
Height = Unit Ht. - 2 3/8

## Metal Cuts

SC-623 header = Unit width - 1/16  
SC-624 tub track = Unit width - 1/16  
SC-625 wall jamb = Unit ht. - 1 3/8

## 1040/1050 Parts List

- A. 2 Wall Jambs
- B. 1 Tub Track with Vinyl
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 4 Clear Jamb Bumpers
- F. 2 Nylon T-Locks
- G. 1 Header
- H. 4 Hanger Brackets
- J. 2 Glass Door Panels
- K. 8 Nylon Bushings (.360 long)
- L. 4 1/4 x 5/8 Flat Head Screws
- M. 4 HD Roller Bearings
- N. 4 #8 x 3/8 Hex Head Screw
- P. 2 Towel Bar Caps (w/Post)
- R. 8 Flat Rubber Washers
- S. 4 Handle Bases (Threaded)
- T. 4 #8 x 5/8 Flat Head Screws
- U. 2 Acylic Towel Bar Assemblies
- V. 3 Clear Panel Guides
- W. 3 #6 x 3/8 Pan Head Screws
- X. 2 Nylon Jamb Covers

