



ALUMAX

BATH ENCLOSURES

300cv Continuous Hinge Shower Door-Frameless

a product of Alcoa

Tel: 800-643-1514
Fax: 870-234-3181

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Door has a continuous extruded ball and socket hinge that is integral to the hinge rail and jamb
- Hinge assembly has a molded bushing attached at the top and bottom of door panel
- Total nominal unit width adjustment is +13/16 -7/16



Calculations

- Maximum allowable width of unit = 37 (@ 72 tall)
- Maximum allowable height of unit = 84 (@ 30 wide)

Glass Size

- Width = Unit width - 3 5/8
- Height = Unit ht. - 1 9/16

Metal Cuts

- SC-508 wall jamb = Unit ht. - 7/16
- SC-552 strike jamb = Unit ht. - 1
- V-351 deflector = Door panel width - 7/16
- SC-649 hinge jamb = Unit ht. - 7/16
- SC-651 hinge rail = Unit ht. - 1 9/16
- SC-915 curb = Unit width

300cv Parts List

- A. 1 Shower Curb
- B. 1 Glazed Door Panel Assembly
- C. 2 Wall Jamb
- D. 6 Plastic Wall Anchors
- E. 6 #8 x 1 1/2 Truss Head Screws
- F. 6 #6 x 3/8 Pan Head Tex Screws
- G. 1 Strike Jamb w/Magnet
- H. 1 Latch Vinyl
- J. 1 Latch
- K. 2 Tubular Handles
- L. 4 Plastic Washers
- M. 2 Plastic Bushings
- N. 2 Cone Head Bolts
- O. 2 Set Screws
- P. 1 Deflector

