



ALUMAX

BATH ENCLOSURES

a product of Alcoa

Tel: 800-643-1514
Fax: 870-234-3181

791c StikStall Shower Door-Framed

www.alumaxbath.com

Product Features

- Available in standard and custom configuration
- Tempered safety glass
- Door has continuous extruded ball and socket hinge that is integral to the hinge rail jamb
- Hinge assembly has a molded bushing attached at the top and bottom of door panel

Metal Cuts

- SC-505 header = Unit width
- SC-505A curb = Unit width
- SC-506 head and curb fill = Top and bottom rail + 5/16
- SC-508 wall jamb = Unit ht. - 3/4
- SC-511 180° post = Unit ht. - 3/4
- SC-549 strike rail = Unit ht. - 3 1/8
- SC-552 strike jamb = Unit ht. - 2
- SC-648 hinge rail = Unit ht. - 3 1/8
- SC-649 hinge jamb = Unit ht. - 2
- SC-589 drip rail = SC-899 bottom rail - 9/16
- SC-899 top and bottom rail = Glass width + 1 7/8

791c Parts List

- A. 1 Curb (with weep slots)
- B. 2 Wall Jamb
- C. 6 Plastic Wall Anchors
- D. 6 #8 x 1 1/2 Truss Head Screws
- E. 2 Plastic Setting Blocks
- F. 1 Fixed Glass Panel
- G. 1 180° Post
- H. 1 Header
- J. 14 #8 x 1/4 Truss Head Screws
- K. 1 Glazed Door Panel
- L. 1 Strike Jamb (Magnetic)
- M. 2 Snap-in Fillers
- N. 1 Drip Rail
- P. 1 #6 x 3/8 Truss Head Screw
- Q. 2 Drip Plugs
- R. 1 Tapered Drip Vinyl
- S. 1 Roll of Double Stick Tape
- T. 1 Interior Door Handle
- U. 1 Exterior Door Handle
- V. 2 #6 x 1 1/8 Round Head Screw
- W. 4 Pcs. Vert. Glazing Vinyl (72)
- X. 2 Pcs. Horiz. Glazing Vinyl (72)

Options

- Towel bar kits
- Glass patterns
- Finish

Calculations

- Maximum allowable width of unit = 72
- Maximum allowable height of unit = 84

Glass Size

- Door glass width as determined
- Door glass ht. = Unit ht. - 5
- Panel glass width = Unit width - door glass width - 5
- Panel glass ht. = Unit ht. - 1

Standard Door Opening Sizes

- 24 9/16 and 29 9/16 width for 68 1/2 unit height
- 24 9/16 and 29 9/16 width for 72 unit height

